

Trusted expertise in domestic and commercial wastewater



Any project, any wastewater application

Wastewater poses a complex challenge, no matter whether it originates in a single house or a multi-family home, a commercial building or an industrial complex. Whatever the property, Sulzer is the ideal wastewater partner from the start of the project to its final sign-off.

Sulzer has vast experience in the handling of domestic and commercial wastewater. We are dedicated to helping professionals design, select, install and service any type of wastewater system. At our disposal are all the solutions needed to keep a building running smoothly.

Our extensive range of products includes drainage pumps, sewage pumps with Contrablock and vortex hydraulics, prefabricated lifting stations for both internal and external installation, and solutions for monitoring and control. These are the result of advanced R&D, built on an engineering heritage comprising over 100 years of pump design and installation.

In total, Sulzer expertise means reliable and efficient pumping with minimized operating costs. Our solutions come with everything you need, ensuring easy, plug-and-play installation with a minimum of time and set-up.



Domestic applications

Domestic properties pose wastewater challenges both large and small. In addition to waste disposal from toilets, there are diverse sources of drainage and grey wastewater including not only sinks and showers, but also drainage from yards and gardens. The high reliability of Sulzer pumps and lifting stations offers security for metropolitan and remote properties alike.

Commercial applications

Commercial properties share many challenges with domestic properties when it comes to pumping and lifting, but their more diverse uses can also mean special demands. Sulzer pumps and lifting stations reliably move not only wastewater with a high proportion of solid or fibrous matter, but also aggressive and even chemically contaminated wastewater. For installations with extreme solid particles, our two-shafted, low speed and high torque grinders will slice through rags and wipes that are loading the pumping stations.


Trusted expertise in domestic and commercial wastewater

Sulzer offers solutions for quick and effective collection of wastewater from residential and public properties, and for transferring it to the municipal wastewater network. Small wastewater pumps, lifting stations, prefabricated pumping stations and equipment for monitoring and control are all a part of the process.

Domestic and commercial wastewater

Wastewater collection network

Wastewater treatment



Our comprehensive product portfolio

Product technology	Product name	Application				Motor-related		Product facts on page
		Domestic	Commercial	Without toilet waste	Waste disposal from toilets	High-efficiency (IE3)	Explosion-proof as standard	
Submersible light and medium duty pumps	Light drainage pump type ABS Robusta 200-300	✓	✓	✓				5
	Light drainage pump type ABS Coronada 250	✓	✓	✓				5
	Light drainage pump type ABS IP 900	✓	✓	✓				5
	Light wastewater pump type ABS MF 154 HW and ABS MF 154-804	✓	✓	✓				5
	Submersible wastewater pump type ABS AS 0530-0841	✓	✓	✓	✓		✓	6
	Submersible grinder pump type ABS Piranha 08-09	✓	✓	✓	✓			6
	Submersible grinder pump type ABS Piranha S 10-30	✓	✓	✓	✓		✓	6
	Submersible grinder pump type ABS Piranha PE and ABS Piranha HH 60 Hz	✓	✓	✓	✓	✓	✓	6
Submersible heavy duty pumps	Submersible sewage pump type ABS XFP 1.3 - 30 kW	✓	✓	✓	✓	✓	✓	6
Lifting stations	Lifting station type ABS Piranhamat 100-120	✓		✓	✓			7
	Lifting station type ABS Sanimax	✓	✓	✓				7
	Lifting station type ABS Nirolift	✓	✓	✓				7
	Lifting station type ABS Sanisett 1 and 2	✓	✓	✓				7
	Lifting station type ABS Piranhamat 701-1002	✓	✓	✓	✓			8
	Lifting station type ABS Sanimat 1000-2002	✓	✓	✓	✓			8
	Lifting station type ABS Sanimat 4002	✓	✓	✓	✓	✓		8
	Lifting station type ABS Synconta 700, 700L, 901B and 902B	✓	✓	✓	✓			9
Sewage grinders	Inline / open channel Muffin Monster™		✓		✓			9
	Channel Monster™		✓		✓			9
Monitoring and control		✓	✓					10

Product overview

Submersible light and medium duty pumps

Light drainage pump type ABS Robusta 200-300

Features and benefits

The Robusta has been designed for pumping clear and wastewater from house, garden or yard and can pump down to a very low water level. It is supplied with built-in level control and check valve and is suitable for manual or automatic operation.

Key characteristics

Capacities	Up to 12 m ³ /h
Heads	8.5 m
Temperatures	40°C, max. 60°C for 5 min
Discharge sizes	G 1¼"
Maximum speed of rotation	2'900 min ⁻¹



Light drainage pump type ABS Coronada 250

Features and benefits

The Coronada is a submersible stainless steel pump for removing clear and aggressive wastewater from areas such as drainage pits, gullies and flooded cellars. Also for drainage of swimming pools, circulation in ponds, and for emptying and filling of containers. Available with KS float switch for automatic level control. A special SX version for particularly aggressive liquids is also available.

Key characteristics

Capacity	9 m ³ /h
Head	7.5 m
Temperatures	40°C, max. 60°C for 5 min
Discharge sizes	G 1¼"
Maximum speed of rotation	2'900 min ⁻¹



Light drainage pump type ABS IP 900

Features and benefits

The ABS light drainage pump IP is a stainless steel pump for corrosive media with vortex hydraulics. It is suitable for pumping aggressive media with a high proportion of solid or fibrous matter. The IP is also ideal for dewatering of chemically contaminated wastewater, industrial effluent, and for use in agriculture.

Key characteristics

Capacity	18 m ³ /h
Head	11 m
Temperatures	40°C, max. 60°C for 5 min
Discharge sizes	G 2"
Maximum speed of rotation	2'900 min ⁻¹



Light wastewater pump type ABS MF 154 HW

Features and benefits

The MF 154HW is a compact submersible pump for the removal of domestic and commercial high temperature wastewater that can contain solids up to 20 mm. The pump has been designed to cover a wide range of internal and external dewatering applications, but primarily where the temperature of the medium exceeds the standard upper limit (40°C) to a maximum allowable temperature of 80°C. Option without KS float switch available.

Key characteristics

Capacity	9 m ³ /h
Head	8 m
Temperatures	80°C
Discharge sizes	1 ½"
Maximum speed of rotation	2'900 min ⁻¹



Light wastewater pump type ABS MF 154-804

Features and benefits

The MF 154-804 is a compact submersible wastewater pump range with vortex impeller for trouble-free operation. The pumps are used for dewatering of buildings and for pumping fluids from low lying locations. Level control switch is an option.

Key characteristics

Capacity	58 m ³ /h
Head	16 m
Temperatures	40°C, max. 60°C for 5 min
Discharge sizes	G 1 1/4"-G 2"/DN 65
Maximum speed of rotation	2'900 min ⁻¹



Submersible wastewater pump type ABS AS 0530-0841

Features and benefits

The AS is a robust and reliable submersible pump for the removal of clear water, wastewater, and sewage from buildings and sites. The pump ranges from 1.0 to 3.0 kW, and is suitable for portable as well as stationary installations. Hydraulics with Contrablock or vortex impellers ensure blockage-free operation.

Key characteristics

Capacity	100 m ³ /h
Head	28 m
Temperatures	40°C, max. 60°C for 5 min
Discharge sizes	DN 50, DN 65, DN 80
Maximum speed of rotation	1'450 min ⁻¹ , 2'900 min ⁻¹



Submersible grinder pumps type ABS Piranha 08-09 / Piranha S 10-30 / Piranha PE / Piranha HH 60 Hz

Features and benefits

Piranha sewage pumps with shredding action provide reliable and economical discharge of effluent under pressure in private municipal and communal schemes. They offer an economical alternative to gravity sewers, and improve environmental protection for pressurized sewer systems.

Key characteristics

Capacity	21 m ³ /h
Head	71 m
Discharge sizes	G 1 1/4" / DN 32-DN 50



Submersible heavy duty pumps

Submersible sewage pumps type ABS XFP 1.3-30 kW

Features and benefits

Designed for use in standard and network pumping stations. Suitable for both wet and dry installation submersible sewage pump type ABS XFP models PE1 to PE3 using premium-efficiency IE3 motors. The XFP pumps offer significant energy saving using IE3 motors, excellent rag handling, long-term reliability and a future proof design.

Key characteristics

Capacity	792 m ³ /h
Head	70 m
Discharge sizes	DN 100-DN 200



Lifting stations

Lifting stations type ABS Piranhamat 100-120

Features and benefits

The Piranhamat 100-120 is designed for domestic wastewater removal from one WC located below the sewer backwash level. It is also possible to connect one wash-hand basin, one shower and one bidet to the unit. The Piranhamat 100-120 is gas- and odour-tight, plug-in-ready, and fitted with a Piranha grinder pump.

Key characteristics

Capacity	5.5 m ³ /h
Head	9 m
Temperatures	40°C, max. 60°C for 5 min
Discharge sizes	DN 25, DN 32



Lifting station type ABS Sanimax

Features and benefits

The Sanimax is a compact lifting station suitable for installation at floor level near the wastewater source below the sewer backwash level. Flood-proof, with an odour-preventing vent system, Sanimax removes wastewater from wash-hand basins, washing machines and showers. Fitted with Robusta or MF pump.

Key characteristics

Capacity	14 m ³ /h
Head	11 m
Temperatures	40°C, max. 60°C for 5 min
Discharge sizes	DN 40
Maximum speed of rotation	2'900 min ⁻¹



Lifting station type ABS Nirolift

Features and benefits

The Nirolift is a synthetic, single pumping station for the pumping of faecal-free wastewater such as the discharge from washing machines, sinks, dishwashers, showers and bathtubs. For below-ground installation in buildings below the sewer level. Fitted with a Robusta, Coronada or MF pump.

Key characteristics

Temperatures	40°C, max. 60°C for 5 min
Discharge sizes	DN 40 with 50 mm Plasson adaptor



Lifting stations type ABS Sanisett 1 and 2

Features and benefits

The Sanisett is a synthetic, single or twin pumping station for the pumping of faecal-free wastewater such as the discharge from washing machines, sinks, dishwashers, showers and bathtubs. For above- or below-ground installation in buildings and areas below the sewer level. Fitted with Robusta, Coronada, IP, Piranha or MF pumps. For applications where pumping must not be interrupted the twin pumping station unit should be installed.

Key characteristics

Temperatures	40°C, max. 60°C for 5 min
Discharge sizes	DN 50 with 63 mm Plasson adaptor



Lifting station type ABS Piranhamat 701

Features and benefits

The Piranhamat 701 is a flood-proof lifting station for automatic sewage removal from areas below the backwash level. This unit is fitted with one ABS Piranha submersible grinder pump suitable for pumping domestic wastewater. This lifting station is ideal for locations where the diameter of the discharge line is restricted.

Key characteristics

Capacity	9 m ³ /h
Head	30 m
Temperatures	40°C, max. 60°C for 5 min
Discharge sizes	G 1¼"
Maximum speed of rotation	2'900 min ⁻¹



Lifting station type ABS Piranhamat 1002

Features and benefits

The Piranhamat 1002 is a two-pump version of the Piranhamat 701 for applications where the additional security of a second pump is required. This unit is fitted with two ABS Piranha submersible grinder pumps.

Key characteristics

Capacity	9 m ³ /h
Head	30 m
Temperatures	40°C, max. 60°C for 5 min
Discharge sizes	G 1¼"
Maximum speed of rotation	2'900 min ⁻¹



Lifting stations type ABS Sanimat 1000-2002

Features and benefits

The Sanimat 1000-2002 is a single pump flood-proof lifting station for automatic removal of domestic wastewater from areas below the backwash level. Robust, synthetic (PE), easy to transport, 70 litre collection tank of compact design.

Key characteristics

Capacity	55 m ³ /h
Head	9.5-18 m
Temperatures	40°C, max. 60°C for 5 min
Discharge sizes	Discharge flange DN 80, plus flanged socket with 4" sleeve and clips (for discharge pipe DN 80/100)
Maximum speed of rotation	1'450 min ⁻¹ , 2'900 min ⁻¹



Lifting station type ABS Sanimat 4002

Features and benefits

The Sanimat 4002 is a flood-proof lifting station for automatic removal of domestic and commercial wastewater from areas below the backwash level. Designed for large buildings, multi-family housing units, hotels, hospitals, etc. Compact design but large storage capacity. Fitted with XFP sewage pumps up to 6 kW.

Key characteristics

Capacity	45 m ³ /h
Head	18 m
Temperatures	40°C, max. 60°C for 5 min
Discharge sizes	Discharge flange DN 80 and DN 100
Maximum speed of rotation	980 min ⁻¹ , 1'450 min ⁻¹



Lifting stations type ABS Synconta 700 and 700L

Features and benefits

The Synconta is a synthetic prefabricated sump. Designed as a single pumping station for the effective dewatering of buildings, and pumping of sewage containing faecal matter from areas below the sewer level.

Key characteristics

Temperatures 40°C, max. 60°C for 5 min
Discharge sizes DN 32



Lifting stations type ABS Synconta 901B and 902B

Features and benefits

Synthetic prefabricated sump, designed as a single or double pumping station for the automatic pumping of wastewater and sewage from locations and areas below the backwash level in accordance with EN 12050-1. Designed as a complete wastewater sump for below-ground installation and for fitting with pumps from the Piranha, AS and MF ranges.

Key characteristics

Temperatures 40°C, max. 60°C for 5 min
Inflow ports DN 100, DN 150, DN 200



Sewage grinders

Muffin Monster™ – Inline/open channel grinders

Features and benefits

Inline and open channel Muffin Monster grinders are designed to protect pumps and other critical equipment from clogs and damage. They shred tough solids in wastewater and rags. The dual-shafted, slow speed and high-torque grinders give a wide grinder capability. The grinders are available with Wipes Ready™ technology which prevents materials from forming long stripes and reweaving.

Key characteristics

Capacities up to 1'558 m³/h
Connections 100 to 500 mm
Pressures up to 6 bar
Cutting chamber up to 1'500 mm



Channel Monster™

Features and benefits

High flow Channel Monster grinders protect inlet works and treatment plants from damaging solids. The rotating screening drums allow fluid to pass through while capturing solids and diverting them to the powerful dual-shafted grinder for shredding. Channel Monsters can protect equipment in commercial wastewater pump stations. The grinders are available with Wipes Ready™ technology which prevents materials from forming long stripes and reweaving.

Key characteristics

Capacities up to 2'775 m³/h
Cutting chamber up to 1'500 mm
Bearing life 100'000 h



Monitoring and control equipment

Leakage relay type ABS CA 461

Features and benefits

CA 461 is designed to detect leakage in pumps and mixers. The amplifier is housed in a norm enclosure fitted for DIN-rail mounting. The unit is available in two executions, 24 VDC or 110-230 VAC supply.

For information about the full range, visit www.sulzer.com



Temperature and leakage relay type ABS CA 462

Features and benefits

CA 462 is designed to spy and detect temperature and leakage in pumps and mixers. The amplifier is housed in a norm enclosure fitted for DIN-rail mounting. The unit is available in two executions, 24 VDC or 110-230 VAC supply.



Pump controller type ABS PC 111 and 211

Features and benefits

The PC 111 and 211 are easy-to-use single (PC 111) and dual-pump (PC 211) controllers designed mainly for use in either gravitation or pressurized municipal wastewater pumping stations. Their numerous features improve pumping station functionality and reliability throughout its life-cycle.



Equipment controller EC 531

Features and benefits


The equipment controller EC 531 is an all-in-one unit for monitoring and control of one or two pumps. It is designated primarily for municipal pumping stations. The software included in the EC 531 is a further development of the PC 441 advanced surveillance systems.



Pump controller type ABS PC 441

Features and benefits

The PC 441 is a monitor and controller for one to four pumps, designed mainly for use in municipal wastewater pumping stations. The PC 441 has many advanced features to minimize operating costs and increase the availability of the pumping station throughout its life cycle. It has an 16-channel analog data logger (2 weeks capacity), and provides a one-week history on counters and accumulators (run time, start count and flow), as well as a time stamp on up to 4'000 pump and alarm events.



Control panel type ABS CP 112-212 / CP 116-216

Features and benefits

These compact control panels are used with either one pump (CP 112, CP 116) or two pumps (CP 212, CP 216) conforming to ATEX. The panels are connected directly to pumps up to 5.5 kW (10 A), 3-phase and single-phase versions, and provides LED indication of power, pump run and alarm. The choice of water level control includes float switches, an analog (4-20 mA) sensor and built-in pressure sensor for closed or open air systems. CP 116-216 have an 8-channel analog data logger (2 weeks capacity), and provides a one-week history on counters and accumulators (run time, start count and flow), as well as a time stamp on up to 4'000 pump and alarm events.



Accessories and software

Float switch type ABS KS

Features and benefits

The KS float switch, used in liquids for control or signal activation, operates in response to the liquid level. It is also suitable for use in sewage and for automatic level control. The KS float switch is impact- and shock-resistant, mercury-free, and environmentally friendly.



ABSEL – Sulzer’s wastewater pump selection program

With ABSEL, you can select specific pumps by configuring the application area, pump series and duty point using the “Hydraulic selection” function. Alternatively, you can navigate through our pump offering by using the “Pump browser”.



Once you have selected a pump, you have the option to download complete product information in PDF format with pump and motor performance curves, a product description, dimensional drawings, operational cost calculations and data sheets.

You can also run a friction loss calculation on dry or wet well applications using the “PipeCalc” function. The “PipeCalc” database contains a wide variety of predefined pipes and fittings such as elbows, valves, transition pieces, inlets and outlets. To provide a first calculation in seconds, the “PipeCalc” function offers you a predefined piping arrangement in a pumping station.



The easy way to navigate in building information modeling (BIM)

Building information modeling (BIM) is an intelligent process for improving collaboration between end users and suppliers in terms of OPEX costs. We have collected the BIM models you need for our lifting stations and submersible pumps in a single location, BIM search at www.sulzer.com/bim. Use the filter to find your product of interest or make a direct entry of the product name.



www.sulzer.com

E10105 en 1.2020, Copyright © Sulzer Ltd 2020
This brochure is a general presentation. It does not provide any warranty or guarantee of any kind. Please, contact us for a description of the warranties and guarantees offered with our products. Directions for use and safety will be given separately. All information herein is subject to change without notice.

